

设置浏览器允许Kerberos身份验证

一. 配置CDH集群监控UI

1) 打开Firefox浏览器, 在地址栏输入about:config, 如图所示:



2) 在搜索栏键入: network.negotiate-auth.trusted-uris, 将监控UI的主机地址输入, 主机之间用逗号分隔

Dev&Stg:

master01. lorealcdh. com, master02. lorealcdh. com, master03. lorealcdh. com, utility. lorealcdh. com, sta-master01. loreal. com, sta-master02. loreal. com, sta-master03. loreal. com, sta-utility. loreal. com, worker01. lorealcdh. com, worker02. lorealcdh. com, worker03. lorealcdh. com, worker04. lorealcdh. com, sta-hbase01. loreal. com, sta-hbase02. loreal. com, sta-hbase03. loreal. com, sta-hbase04. loreal. com, sta-worker01. loreal. com, sta-worker02. loreal. com, sta-worker03. loreal. com, sta-worker04. loreal. com, sta-kafka01. loreal. com, sta-kafka02. loreal. com, sta-kafka03. loreal. com

Production:

hbase01. loreal. com, hbase02. loreal. com, hbase03. loreal. com, hbase04. loreal. com, master01. loreal. com, master02. loreal. com, master

3) 搜索: network.auth.use-sspi, 修改为false

4) 2种方式, 这里只需配置MIT_Kerberos就可以了。打开MIT Kerberos Ticket Manager, Get Ticket

a) DEV

Principal:hive@LOREALCDH.COM

b) STG

Principal:hive@LOREAL.COM

5) 打开Firefox, 访问Yarn监控UI

a) DEV

<http://master03.lorealcdh.com:8088/cluster>

b) STG

<https://sta-master03.loreal.com:8090/cluster>

6) To do