

centos7 openldap双主部署

<https://blog.csdn.net/fanren224/article/details/79707206>

亲测 可用。

openldap启用日志功能

<https://blog.csdn.net/fanren224/article/details/80532277>

```
vi mod_syncprov.ldif
```

```
# create new
dn: cn=module,cn=config
objectClass: olcModuleList
cn: module
olcModulePath: /usr/lib64/openldap
olcModuleLoad: syncprov.la
```

```
vim syncprov.ldif
```

```
# create new
dn: olcOverlay=syncprov,olcDatabase={2}hdb,cn=config
objectClass: olcOverlayConfig
objectClass: olcSyncProvConfig
olcOverlay: syncprov
olcSpSessionLog: 100
```

```
vim master02.ldif
```

```
# create new
dn: cn=config
changetype: modify
replace: olcServerID
# specify uniq ID number on each server
olcServerID: 1
dn: olcDatabase={2}hdb,cn=config
changetype: modify
add: olcSyncRepl
olcSyncRepl: rid=001
    provider=ldap://172.20.85.29:389/
    bindmethod=simple
    binddn="cn=admin,dc=baofoo,dc=com"
    credentials=baofoo@64
    searchbase="dc=baofoo,dc=com"
    scope=sub
```

```
schemachecking=on  
type=refreshAndPersist  
retry="30 5 300 3"  
interval=00:00:05:00
```

```
add: olcMirrorMode  
olcMirrorMode: TRUE  
dn: olcOverlay=syncprov,olcDatabase={2}hdb,cn=config  
changetype: add  
objectClass: olcOverlayConfig  
objectClass: olcSyncProvConfig  
olcOverlay: syncprov
```