

oozie 命令行操作

```
oozie jobs -filter user=xy_app_spark
```

```
oozie jobs -filter status=RUNNING
```

```
oozie jobs -jobtype coordinator
```

```
oozie job -kill [id]
```

oozie调用ssh 突然中断的解决办法:

修改数据库

```
select id, status from COORD_JOBS where id='0164425-190322163632437-oozie-oozi-C';
```

```
update COORD_JOBS set status='SUCCEEDED' where id = '0164425-190322163632437-oozie-oozi-C';
```

注意老版本的oozie要带地址

批量删除SUSPENDED 状态的任务

```
oozie jobs -filter Status=SUSPENDED -kill --oozie=http://cdh81-40:11000/oozie/ -len 3000000 | wc -l
```

```
[root@cdh81-50 ~]#  
[root@cdh81-50 ~]#  
[root@cdh81-50 ~]# oozie jobs -filter Status=SUSPENDED --oozie=http://cdh81-40:11000/oozie/ -len 3000000 | wc -l  
36978  
[root@cdh81-50 ~]# oozie jobs -filter Status=SUSPENDED -kill --oozie=http://cdh81-40:11000/oozie/ -len 3000000 | wc -l
```

查找调度

```
oozie jobs -jobtype coordinator --oozie=http://cdh81-40:11000/oozie/
```

